




 Walk behind machine
with or without traction


 Battery autonomy
2 - 4 h


 Operating tension
24 V / 110 Ah

 Cleaning width
550 mm

 Solution tank / recovery tank
40 / 45 l

 Disc brushes
2 x 285 mm

 Brushes pressure adjustable
max. 24,5 kg


 Brushes speed
280 rpm



Theoretical working capacity

1925 / 2200 m²/h

Technical data

Squeegee width	770mm
Brushes motor	420 Watt
Type of drive	semi-automatic/automatic
Maximum gradient	2%
Suction motor	570 Watt
Suction vacuum	120 mbar
Machine dimensions	
length	1140 mm
height	1053 mm
width without squeegee	586 mm
Machine weight without batteries	74 / 84kg
Traction motor	-- / 120 Watt
Movement speed	-- / 4 km/h
Battery compartment	
length	342 mm
width	350 mm
height	300 mm
Class	
Protection level	IP 23
Noise level	66,2 / 67,6 dB (A)

Floor scrubbing machine, battery-driven, with brushes base group of 55 cm.

The two models differ from the presence or not of the traction system.

The brushes pressure is adjustable from the operator in function of the floor to be cleaned.

In the semi-automatic version the brushes inclination can be adjusted for easy driving.

Thanks to the solid structure, the easiness of maintenance and the simplicity of the controls, working with the ruby becomes simple obtaining an elevated leaning quality.

